

# MATERIAL SAFETY DATA SHEET

EFFECTIVE DATE: January 1, 2007

# “SATAC”

## Cellulose Insulation

### CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:	“SATAC” INSULATION	MANUFACTURER: FIBERLITE TECHNOLOGIES, Inc..
Chemical Formula:	$(C_1H_{15}O_5)-Na_2SO_4 \cdot H_3BO_3$	3605 E. 25 <sup>th</sup> Street
Chemical Name/Synonyms:	Cellulose Insulation	Joplin, MO 64804-3224
Chemical Family:	Cellulose Treated With Inorganic Salts	www.fiberlitetech.com
CAS Registry Number:	Not Established	<b>EMERGENCY PHONE NUMBER:</b>
TSCA Inventory Number:	Not Listed	<b>Fiberlite Technologies, Inc. 417-781-6380</b>

### COMPOSITION/INFORMATION ON INGREDIENTS OSHA HAZARDS

This product contains less than 99 percent (%) boric acid ( $H_3BO_3$ ) CAS No. 10043-35-3. Boric acid is added in the form Zone Defense®, EPA Reg. No. 44757-3 for purposes of superior fire and insecticide properties within the insulation which are beneficial to this building material. Board Defense® (disodium octaborate tetrahydrate), EPA Reg. No. 44757-20 is a fungicide added for mold control within the insulation and is also beneficial to this building material. This product contains wood fiber (milled newsprint) CAS No. 65996-61-4, corrugated kraft (milled) CAS No. None Assigned, bleach sulfite board (milled) CAS No. None Assigned. Regarding information on the chronic and ecological toxicity of this product, we have reviewed the available medical and toxicological literature for 100% boric acid. Boric acid can be used in an identical manner, is chemically very similar to and slightly more toxic than comparable concentrations and exposures to disodium octaborate tetrahydrate. Boric acid is hazardous under the OSHA Hazard Communication Standard based on animal chronic toxicity studies.

### HAZARD IDENTIFICATION

#### EMERGENCY OVERVIEW:

“SATAC” INSULATION is an odorless wood fiber insulation material. The product is not flammable, combustible, or explosive, and it presents no unusual hazard if involved in a fire. “SATAC” INSULATION presents little or no hazard (to humans) and has low acute oral and dermal toxicities. Care should be taken to minimize the amount of “SATAC” INSULATION released to the environment to avoid ecological effects.

#### POTENTIAL ECOLOGICAL EFFECTS:

Large amounts of “SATAC” INSULATION can be harmful to boron-sensitive plants and other ecological systems.

#### POTENTIAL HEALTH EFFECTS:

**Routes of Exposure:** Inhalation is the most significant route of exposure in occupational and other settings. Dermal exposure is not usually a concern because “SATAC” INSULATION is not absorbed through intact skin.

**Inhalation:** Occasional mild irritation of nose and throat may occur from inhalation of “SATAC” INSULATION dusts at levels greater than 10 mg/m<sup>3</sup>.

**Eye Contact:** “SATAC” INSULATION is non-irritating to eyes in normal industrial use.

**Skin Contact:** “SATAC” INSULATION does not cause irritation to intact skin

**Ingestion:** “SATAC” INSULATION is not intended for ingestion. “SATAC” INSULATION has a relatively low acute toxicity. Small amounts (e.g. 3 teaspoonfuls) swallowed accidentally are not likely to cause effects; swallowing amounts larger than that may cause gastrointestinal symptoms.

**Cancer:** “SATAC” INSULATION is not considered a carcinogen.

**Reproductive:** Long-term, high dose animal ingestion studies of similar inorganic borate chemicals at significantly higher concentrations have demonstrated reproductive effects in male animals. A human study of occupational exposure to borate dust showed no adverse effect to reproduction.

**Developmental:** High dose animal ingestion studies of similar inorganic borate chemicals at significantly higher concentrations have demonstrated developmental effects in fetuses of pregnant animals, including fetal weight loss.

**Target Organs:** No target organ has been identified in humans. High dose animal ingestion studies of similar inorganic borate chemicals at significantly higher concentrations indicate the testes are the target organs in male animals.

**Signs and Symptoms of Exposure:** Symptoms of accidental over-exposure to borate products have been associated with ingestion or by absorption through large areas of damaged skin. These may include nausea, vomiting, and diarrhea, with delayed effects of skin redness and peeling. Refer to Toxicology Information Section for details on Toxicological Data.

## FIRST AID MEASURES

**Inhalation:** No specific treatment is necessary since “SATAC” INSULATION is not likely to be hazardous by inhalation. Prolonged exposure to dust levels in excess of regulatory limits should always be avoided.

**Eye Contact:** Use eye wash fountain or fresh water to cleanse eye. If irritation persists for more than 30 minutes, seek medical attention.

**Skin Contact:** No treatment necessary because non-irritating.

**Ingestion:** Swallowing less than one teaspoon will cause no harm to healthy adults. If larger amounts are swallowed, give two glasses of water to drink and seek medical attention.

**NOTE TO PHYSICIANS:** Observation only is required for adult ingestion of a few grams of “SATAC” INSULATION. For ingestion in excess of larger amounts, maintain adequate kidney function and force fluids. Gastric lavage is recommended for symptomatic patients only. Hemodialysis should be reserved for massive acute ingestion or patients with renal failure. Boron analyses of urine or blood are only useful for documenting exposure and should not be used to evaluate severity of poisoning or to guide treatment.

## FIRE FIGHTING MEASURES

**General Hazard:** None, because “SATAC” INSULATION is not flammable, combustible or explosive. The product itself is a flame retardant.

**Extinguishing Media:** Any fire extinguishing media may be used on nearby fires.

**Flammability Classification (29 CFR 1910, 1200):** Non-flammable solid.

## ACCIDENTAL RELEASE MEASURES

**General:** “SATAC” INSULATION contains water-soluble inorganic salts that may cause damage to trees or vegetation by root absorption. (Refer to Ecological information for specific information)

**Land Spill:** Vacuum, shovel or sweep up “SATAC” INSULATION and place in containers for disposal in accordance with applicable local regulations. Avoid contamination of water bodies during clean up and disposal. No personal protective equipment is needed to clean up land spills

**Water Spill:** “SATAC” INSULATION will cause localized contamination of surrounding waters depending on the quantity dissolved in these waters. At high concentrations some damage to local vegetation, fish and other aquatic life may be expected. “SATAC” INSULATION is a non-hazardous waste when spilled or disposed of, as defined in the Resource Conservation and Recovery Act (RCRA) regulations (40 CFR 261). (Refer to Regulatory Information for additional references and information regarding California regulations.)

## HANDLING AND STORAGE

**Storage Temperature:** Ambient

**Storage Pressure:** Atmospheric

**Special Sensitivity:** None known

**General:** No special handling precautions are required, but dry, indoor storage is recommended. To maintain package integrity, bags should be handled on a "first-in first-out" basis. Good housekeeping procedures should be followed to minimize dust generation and accumulation.

## EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Use local exhaust ventilation to keep airborne concentrations of “SATAC” INSULATION dust below permissible exposure levels.

**Personal Protection:** Where airborne concentrations are expected to exceed exposure limits, NIOSH/MSHA certified respirators must be used. Eye goggles and gloves are not required for normal industrial exposures, but may be warranted if environment is excessively dusty.

**Occupational Exposure Limits:** “SATAC” INSULATION is listed/regulated by OSHA, Cal OSHA and ACGIH as "Particulate Not Otherwise Classified" or "Nuisance Dust".

OSHA: PEL*	15 mg/m <sup>3</sup> total dust and 5 mg/m <sup>3</sup> respirable dust
ACGIH: TLV**	10 mg/m <sup>3</sup>
Cal OSHA: PEL*	10 mg/m <sup>3</sup>

\*PEL="Permissible Exposure Limit"

\*\*TLV-"Threshold Limit Value"

## PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Gray, odorless fiber	<b>Boiling Point:</b>	Not Applicable
<b>Specific Gravity:</b>	0.7 compressed	<b>Melting Point:</b>	Not Applicable
<b>Vapor Pressure:</b>	Negligible @ 20°C	<b>Flash Point:</b>	Not Applicable
<b>Solubility in Water:</b>	Fiber is not soluble; Chemical additive is soluble at the rate of 4.7% @ 20° C.	<b>pH:</b>	7.4 (2.0% solution @ 25°C)
		<b>Viscosity:</b>	Not Applicable

## STABILITY AND REACTIVITY

**General:** “SATAC” INSULATION is a stable product.

**Incompatible Materials and Conditions to Avoid:** Reaction with strong reducing agents such as metal hydrides or alkali metals will generate hydrogen gas which could create an explosive hazard.

**Hazardous Decomposition:** None

## TOXICOLOGICAL INFORMATION

**NOTE:** “SATAC” INSULATION contains 13.76% boric acid, and 86.24% inert wood fiber with conditioners. The boric acid data discussed in this section relates to 100% pure boric acid.

**INHALATION:** Human epidemiological studies show no increase in pulmonary disease in occupational populations with chronic exposures to boric acid dust and sodium borate dust.

**CARCINOGENICITY:** A Technical Report issued by the National Toxicology Program showed “no evidence of carcinogenicity” from a full 2-year bioassay on boric acid in mice at feed doses of 2500 and 5000 ppm in the diet. No mutagenic activity was observed for boric acid in a recent battery of four short-term mutagenicity assays.

**REPRODUCTIVE/DEVELOPMENTAL TOXICITY:** Animal studies indicate boric acid reduces or inhibits sperm production, causes testicular atrophy, and, when given to pregnant animals during gestation, may cause developmental changes. These feed studies were conducted under chronic exposure conditions leading to doses many times in excess of those that could occur through inhalation of dust in occupational settings.

**Reproductive Toxicity (Fertility):** Dietary boric acid levels of 6,700 ppm in chronic feeding studies in rats and dogs produced testicular atrophy, while dogs and rats receiving 2000 ppm did not develop testicular changes (<sup>1</sup>Weir, Fisher, 1972). In chronic feeding studies of mice on diets containing 5000 ppm (550 mg/kg/d) boric acid, testicular atrophy was present while mice fed 2500 ppm (275 mg/kg/d) boric acid showed no significant increase in testicular atrophy (<sup>2</sup>NTP, 1987). In another boric acid chronic study, in mice given 4500 ppm (636mg/kg/d), degeneration of seminiferous tubules was present together with a reduction of germ cells, while at 1000 ppm (152 mg/kg/d) no effect was seen (<sup>3</sup>Fail et al., 1991). In a reproduction study on rats, 2000 ppm of dietary boric acid had no adverse effect on lactation, litter size, weight and appearance (<sup>1</sup>Weir, Fisher, 1972). In a continuous breeding study in mice there was reduction in fertility rates for males receiving 4500 ppm (636 mg/kg/d) boric acid, but not for females receiving 4500 ppm boric acid (<sup>3</sup>Fail et al., 1991)

**Developmental Toxicity:** Boric acid at dietary levels of 1000 ppm (78 mg/kg/d) administered to pregnant female rats throughout gestation caused a slight reduction in fetal weight, but was considered to be close to the NOAEL. Doses of 2000 ppm (163 mg/kg/d) and above caused fetal malformations and maternal toxicity. In mice the no effect level for fetal weight reduction and maternal toxicity was 1000 ppm (248 mg/kg/d) boric acid. Fetal weight loss was noted at dietary boric acid levels of 2000 ppm (452 mg/kg/d) and above. Malformations (ageneses or shortening of the thirteenth rib) were seen at 4000 ppm (1003 mg/kg/d), (<sup>4</sup>Heindel et al., 1992).

<sup>1</sup> (Weir, R.J. and Fisher, R.S., Toxicol. Appl. Pharmacol., 23:351-364 (1974))

<sup>2</sup> (National Toxicology Program (NTP)-Technical Report Series No. TR324, NIH Publication NO. 88-2580 (1987),PB88-213475/XAB)

<sup>3</sup> (Fail et al., Fund. Appl. Toxicol. 17, 225-239 (1991))

<sup>4</sup> (Heindel et al., Fund Appl. Toxicol. 18, 266-277 (1992))

## ECOLOGICAL INFORMATION

### ECOTOXICITY DATA:

**Phytotoxicity:** Although boron is an essential micronutrient for healthy growth of boron-sensitive plants, it can be harmful to plants in higher quantities. Plants and trees can easily be exposed by root absorption to toxic levels of boron in the form of water-soluble borate leached into nearby soil or waters. Care should be taken to minimize the amount of borate product released to the environment.

**Fish Toxicity:** Boron naturally occurs in sea water at an average concentration of 5 mg B/liter. In laboratory studies the acute toxicity (96-hr LC<sub>50</sub>) for under-yearling Coho salmon (*Opestrichthys kisutch*) in sea water was determined as 40 mg B/L (added as sodium metaborate). Boron concentrations in fresh surface waters are generally less than 1 mg B/L. Laboratory studies on the toxicity

## Fiberlite Technologies, Inc. – “SATAC” INSULATION – Page 4

of freshwater fish were determined using early life (embryo-larval) stages in natural water and Boric Acid as a test substance. The results were:

- Rainbow Trout (*S. gairdneri*)
  - 24-day LC<sub>50</sub>=150.0 mg B/L
  - 36-day NOEC•LOEC=0.75-1 mg B/L
- Goldfish (*Carassius auratus*)
  - 7-day NOEC•LOEC=26.50 mg B/L
  - 3-day LC<sub>50</sub>=178 mg B/L

**Invertebrate Toxicity:** The acute toxicity (48-hour LC<sub>50</sub>) to Daphnids (*Daphnia magna* Straus) in natural water is reported to be 133 mg B/L (added as Boric Acid). Estimated chronic toxicity (21-day NOEC•LOEC) values of 6-13 mg B/L (added as Boric Acid) have also been reported.

### **ENVIRONMENTAL FATE DATA:**

**Persistence/Degradation:** Boron is naturally occurring and ubiquitous in the environment. Boric acid decomposes in the environment to natural borate.

**Soil Mobility:** The boric acid additive in “SATAC” INSULATION is soluble in water and is leachable through normal soil.

NOTE: Boron (B) is the element in “SATAC” INSULATION which is used to characterize borate ecological effects. To convert “SATAC” INSULATION data to Boron (B), multiply by 0.0235.

## DISPOSAL CONSIDERATIONS

**Disposal Guidance:** Small quantities of “SATAC” INSULATION can usually be disposed of at Municipal Landfill sites. No special disposal treatment is required, but refer to state and local regulations for applicable site-specific requirements. Tonnage quantities of product are not recommended to be sent to landfills. Such product should, if possible, be re-used for an appropriate application.

**RCRA (40 CFR 261):** “SATAC” INSULATION is not listed under any sections of the Federal Resource Conservation and Recovery Act (RCRA).

## TRANSPORT INFORMATION

**DOT Hazardous Material Classification:** “SATAC” INSULATION is not a U.S. Department of Transportation (DOT) Hazardous Material.

**DOT Hazardous Substance Classification:** “SATAC” INSULATION is not a DOT Hazardous Substance.

**International Transportation:** “SATAC” INSULATION has no U.N. Number, and is not regulated under international rail, highway, water, or air transport regulations.

## REGULATORY INFORMATION

**TSCA No.:** “SATAC” INSULATION does not appear on the EPA TSCA inventory list. Boric Acid appears on the EPA TSCA inventory list under the CAS No. 10043-35-3.

**RCRA:** “SATAC” INSULATION is not listed as a hazardous waste under any sections of the Resource Conservation and Recovery Act or regulations (40) CFR 261 et seq.).

**Superfund:** CERCLA/SARA. “SATAC” INSULATION is not listed under CERCLA (the Comprehensive Environmental Response Compensation and Liability Act) or its 1986 amendments, SARA, (the Superfund Amendments and Reauthorization Act), including substances listed under Section 313 of SARA, Toxic Chemicals, 42 USC 11023, 40 CFR 372.65; Section 302 of SARA, Extremely Hazardous Substances, 42 USC 11002, 40 CFR 355; or the CERCLA Hazardous Substances list, 42 USC 9604, 40 CFR 302.

**Safe Drinking Water Act:** “SATAC” INSULATION is not regulated under the SDWA, 42 USC 300g-1, 40 CFR 141 et seq. Consult state and local regulations for possible water quality advisories regarding boron.

**Clean Water Act (Federal Water Pollution Control Act):** 33 USC 1251 et seq.

- a.) “SATAC” INSULATION is not itself a discharge covered by any water quality criteria of Section 304 of the CWA, 33 USC 1314.
- b.) It is not on the Section 307 List of Priority Pollutants, 33 USC 1317, 40 CFR 129
- c.) It is not on the Section 311 List of Hazardous Substances, 33 USC 1321, 40 CFR 116.

**OSHA/Cal OSHA:** This MSDS document meets the requirements of both OSHA (29 CFR 1910.1200) and Cal OSHA (Title 8 CCR 5194(g)) hazard communication standards. Refer to Exposure Control/Personal Protection for regulatory exposure limits.

**IARC:** The International Agency for Research on Cancer (of the World Health Organization) does not list or categorize “SATAC” INSULATION as a carcinogen.

**NTP Annual Report on Carcinogens:** “SATAC” INSULATION is not listed.

## Fiberlite Technologies, Inc. – “SATAC” INSULATION – Page 5

**OSHA Carcinogen:** “SATAC” INSULATION is not listed.

**California Proposition 65:** “SATAC” INSULATION is not listed on any Proposition 65 lists of carcinogens or reproductive toxicants.

### **OTHER INFORMATION**

**National Fire Protection Association (NFPA) Classification:**

Health - 0, Flammability - 0, Reactivity 0\*

**Hazardous Materials Information Systems (HMIS):**

Red: (Flammability) - 0, Yellow: (Reactivity) - 0, Blue: (Acute Health) - 1\*

\*Chronic Effects

*Information presented herein has been compiled from sources considered dependable and is accurate and reliable to the best of our knowledge and belief, but it is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any law or regulation. It is the user's responsibility to determine the suitability of any material for a specific purpose and adopt necessary safety precautions. We make no warranty as to results to be obtained in using any material and, since conditions or use are not under our control, we must necessarily disclaim all liability with respect to use of any material supplied by us.*

*Replaces “SATAC” Cellulose Insulation MSDS Dated January 1,2005*

For more information contact Fiberlite Technologies, Inc. 800-641-4296